

ISUZU F-SERIES BUS


BUILT FOR YOUR JOURNEY















ISUZU FRR90 Bus

SPECIFICATION	FRR90 BUS
SEATS	
Seat Configuration	50 (3 x 2 sitting configuration with priority seats)
ENGINE(CC)	
Model	4HK1- TCC
Туре	Diesel, Turbocharged with Intercooler, Electronic Controlled, Common Rail Direct Fuel Injection
Capacity	5193 cc
No. of Cylinders	4
Power kW (hp) @ rpm	140(190) @ 2,600
Torque kgm (Nm) @ rpm	52(510) @ 1,600
Emission Standards	Euro IV
TRANSMISSION	
No. of Gears	6 Speed (6F/1R)
Drive Train	4x2
Shift	Manual
FGR	6.833
SUSPENSION	
Front Suspension	Multi Leaf Spring Shock Absorbers - Double acting, with front stabilizer
Rear Suspension	Multi Leaf Spring with Helper Spring paired with shock absorbers - double acting and with rear stabilizer
СLUТСН	
Туре	Dry single plate, 14"
Operation	Hydraulic control, Air Assist
STEERING	
Operation	Power Assisted
Tilt	Standard
BRAKES	
Service Brakes	Air Over Hydraulic, dual circuits, with air dryer
Auxilliary Brakes	Exhaust brake
DIMENSIONS	
Wheel Base (mm)	5300
Overall Length (mm)	9760
Overall Width (mm)	2500
Overall Height (mm)	3283
MASS	
GVW(Kgs)	10400
Front Axle	3600
Rear Axle	7700
FUEL TANK (Lts)	
Capacity	200
TYRES	
Tire Size	265/75R19.5
Rim Size	19.5 x 6.75 RIMS
Warranty	12months or 100,000km whichever comes first









